





With a modern design and a variety of first-in-segment features, the all-new TVS Jupiter is tailored to offer the best of technology, comfort, convenience, style, and safety.



INTRODUCING

THE ALL-NEW TVS JUPITER WITH FEATURES, WHICH WILL DELIGHT YOU AND YOUR FAMILY.

1ST IN SEGMENT























1ST IN SEGMENT



TECHNOLOGY

THAT HELPS YOU STAY CONNECTED, ALWAYS.



1ST IN SEGMENT

FULLY-DIGITAL COLOURED CLUSTER Use tech to your advantage.


















ALL-NEW REFINED ENGINE



SILENT START





An **innovative technology** where performance meets mileage. Gives 10% more mileage* and better pickup just when you need it.

KEEP YOUR **LOVED ONES SAFE.**



STURDY AND DURABLE BUILD FOR ENHANCED PROTECTION



LIGHTS UP YOUR PATH



YOUR RIDE MADE SAFER -AUTO OFF INDICATORS



ALERT OTHER RIDERS DURING SUDDEN BRAKE

CONVENIENCE

FOR EVERY NEED & FOR EVERYONE.



FUELING YOUR VEHICLE HAS NEVER BEEN EASIER



POWER YOUR DEVICES ON THE GO



CARRY EVERYTHING YOU NEED AND MORE



UNLOCK YOUR SEAT AND FUEL TANK WITH A SINGLE KEY

YOUR RIDES ARE COMFORTABLE.





BETTER BALANCE AND STABILITY ON EVERY TERRAIN



EXPERIENCE SUPERIOR HANDLING AND STABILITY



NEVER FALL SHORT ON COMFORT



GO THROUGH ROUGH TERRAIN WITH EASE

ELEGANT COLOURS.





Product	Colour	iGO Assist	SmartXonnect	Signature Infinity Light Bar
Drum		_	_	_
Drum Alloy		_	_	_
Drum SmartXonnect		✓	✓	✓
Disc SmartXonnect		~		

SPECIFICATIONS

ENGINE (BS-VI compliant)

Type Single cylinder, 4-stroke,

CVTi, fuel injection

Displacement 113.3 cc

Bore x Stroke 51 x 55.5 mm

Air Filter Type Paper filter

Maximum Power 5.9 kW @ 6500 rpm

Maximum Torque 9.8 Nm @ 5000 rpm (with assist)

9.2 Nm @ 5000 rpm (without assist)

Transmission Type CVT automatic

Starting System Kick* and electric starter

ELECTRICALS

Ignition ECU-controlled ignition

Battery 12V, 5Ah (SmartXonnect variant) MF battery

12V, 4Ah (Drum and Drum Alloy) MF battery

Headlamp LED
Tail Lamp LED

CHASSIS & SUSPENSION

Dimensions (I*h*b) 1848 x 665 x 1258 mm

Wheelbase 1275 mm

Ground Clearance 163 mm (unladen)
Front Suspension Telescopic hydraulic

Rear Suspension Twin tube emulsion type shock absorber

with 3-step adjustment.

BRAKES & TYRES

Front 220 mm Disc*, 130 mm Drum variant

Rear 130 mm Drum

Tyre Size (Front & Rear) 90/90-12-54 J (tubeless)







